## UNCLASSIFIED

AD

401 278

## DEFENSE DOCUMENTATION CENTER

**FOR** 

SCIENTIFIC AND TECHNICAL INFORMATION

CAMERÓN STATION, ALEXANDRIA, VIRGINIA



UNCLASSIFIED

MOTICE: When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

STEP AUTHORS:

Dmitriyeva, N. N., Dmitriyev, V. A.

TITLE:

The distortion of an ionization burst spectrum effected by an amplifier

PERIODICAL Discow. Universitet. Vestnik. Scriya III. Pisika, astronomiya, no. 6, 1962 77-10

TEXT: The distortion of pulses, i.e. the variation of the amplitude ratios, of a cylindrical ionization chamber was analyzed at various ionization distributions in the chamber. The case of an amplifier with broad pass-band ( $\tau_1 = 10T$ ,  $\tau_2 = 1/5T$ ) is investigated and some other cases, e.g. an amplifier with  $\tau_1 = \tau_2 = T$ , are discussed. T is the pulse duration,  $\tau_1$  and  $\tau_2$  are time constants of the most extreme differentiation and integration terms of the amplifier. The scattering and the magnitude of the output signals are compared for various values of  $\tau_1$ ,  $\tau_2$ , T, and for various ionization distributions in the chamber. For  $\tau_1 = \tau_2 = T$ , the slope front Card 1/2

The distortion of an ionization...

S/188/62/000/006/002/016 B191/B102

increases by  $\leq 10\%$  and the pulse-height resolution is found to be 3%. For  $\tau_1 = \tau_2 > T$ , a smaller scattering is, however, always accompanied by a considerable increase in the slope front (several 100%). A method of tuning band width noise, and magnitude of T for certain purposes (with consideration of microphony) is discussed. There are 2 figures and 1 tables

ASSOCIATION: Kafedra kosmicheskikh luchey (Department of Cosmic Radiation)

SUBMITTED: February 26, 1962